

Order number: 01 274 06 99

SCHELL electronic wash basin mixer MODUS E HD-M

(high pressure mixed water)
vandal-resistant valve body
mains operation 12 V, ca. 430 mm connection cable with plug, protection category IP 65, incl. transformer plug, 100 - 240 V, 50 - 60 Hz

Scope of delivery:

- infrared sensor single hole tap
- electronic module with program for adjustment control and part time stagnation flush program (permanent flush 20 s/24 h flush)
- cartridge solenoid valve 6 V
- 2 flexible hoses Clean-Fix S G3/8 int. thread x 380 mm with integrated backflow preventer (BP, DIN EN 1717: EB)
- 2 prefilters
- flow regulator
- wash basin mounting accessories

Field of application / Technical data:

- flow volume: max. 5 l/min independent of pressure
- flow pressure: 1 - 5 bar
- Max. resting pressure 8 bar
- Water temperature max. 70°C (80°C permissible for 10 min./day)

Details:

- Material: housing out of brass conform German drinking water regulation, cover of battery compartment out of plastic
- Test Mark: P-IX 28338/IO, Belgaqua
- Surface: chrome
- Weight: 1.66 kg/pc.
- Packaging unit: 1

Versions:

battery operation 9 V, incl. 9 V alkaline battery Order No.: [01 276 06 99](#)
electronic module with battery level indicator, chrome,
PU 1, W: 1.79 kg/pc.

Recommended associated item:

flow regulator, UNIVERSAL, theft safe Order No.: [02 121 06 99](#)
angle valve thermostat Order No.: [09 406 06 99](#) or
regulating angle valve with normal filter with ASAG Order No.: [05 428 06 99](#) or
easy
regulating angle valve with normal filter without ASAG Order No.: [05 429 06 99](#) or
easy
sampling angle valve Order No.: [03 835 06 99](#)
Pressure Balance Valve PBV Order No.: [06 558 12 99](#)
extension cable 1,5 m Order No.: [01 550 00 99](#)

