

# WC element for dry-wall ViConnect Pro

## PRODUCT INFORMATION

### 1 . POSITION



<b>Model</b>	<b>922142</b>
Collection	ViConnect Pro
Width	500 [mm]
Height	1120 [mm]
Depth	135 [mm]
Weight	15 [kg]
Description	<p>For dry-wall construction; standard height for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc.; for dry-wall construction; adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm; adjustment range front to wall: 135-205mm (when mounted on wall brackets); 4-point fastening with wall brackets; includes support feet and fastening materials for installation in front of wall, sideways or in corners; with protection cap for the flushing pipe; 2 times M12 WC retaining bolts adjustable to 180mm with protection plugs and nuts; installation instructions; without flush plate; Individual packaging materials;</p> <p>For combination with als wall-hung WC (incl. SupraFix WWC, WWC with shortened back panel and WC with extended radius); combinable with Aquareduct ceramics (LEED points: 4); self-supporting powder-coated steel frame; fully pre-assembled; front operated; mechanical push button transmission to drain fitting; with protection cap for the flushing pipe; concealed cistern with insulation against condensation with dual flush 3/6l, adjustable to 3/4,5l, maximal flush quantity 7,5l, filling valve Noise Class I, flexible hose for filling valve, can be tightened by hand, 2-part angle valve connection set R1/2, mounting clip for drain bend, 4 adjustment settings, protection box for access opening can be cut to size, with depth-adjustable WC connecting bend 90° DN 90 (Ø90) / with reducing sleeve DN 90 (Ø90)/DN 100 (Ø110) with protection cap, complete WC connection set DN 90 (Ø90)/180mm, certification marks for concealed cistern: Noise Class I</p>
Specification text	For dry-wall construction; standard height; size 500 x 1120 x 135 mm; for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc.; for dry-wall construction; adjustment range of feet from unfinished floor level

to upper edge of finished floor level: 0-200mm; adjustment range front to wall: 135-205mm (when mounted on wall brackets);  
 4-point fastening with wall brackets; includes support feet and fastening materials for installation in front of wall, sideways or in corners; with protection cap for the flushing pipe; 2 times M12 WC retaining bolts adjustable to 180mm with protection plugs and nuts; installation instructions; without flush plate; Individual packaging materials;  
 For combination with als wall-hung WC (incl. SupraFix WWC, WWC with shortened back panel and WC with extended radius); combinable with Aquareduct ceramics (LEED points: 4); self-supporting powder-coated steel frame; fully pre-assembled; front operated; mechanical push button transmission to drain fitting; with protection cap for the flushing pipe; concealed cistern with insulation against condensation with dual flush 3/6l, adjustable to 3/4,5l, maximal flush quantity 7,5l, filling valve Noise Class I, flexible hose for filling valve, can be tightened by hand, 2-part angle valve connection set R1/2, mounting clip for drain bend, 4 adjustment settings, protection box for access opening can be cut to size, with depth-adjustable WC connecting bend 90° DN 90 (Ø90) / with reducing sleeve DN 90 (Ø90)/DN 100 (Ø110) with protection cap, complete WC connection set DN 90 (Ø90)/180mm, certification marks for concealed cistern: Noise Class I

## COLOURS

None	92214200	4051202483197